

Engine Model: KT38-M
634KW/850HP 1800RPM

GENERAL ENGINE DATA

Type	4 Cycle, 60° Vee, Turbocharged & Aftercooled
Cylinders.....	12
Bore	mm [in] 159 [6.25]
Stroke	mm [in] 159 [6.25]
Displacement	liter [in ³] 38 [2,301]

ENGINE MOUNTING & ACCESSORY DRIVES

Max. Allowable Bending Moment at Rear Face of Block	N·m [ft·lb]	6101 [4500]
Max. Allowable Axial Thrust Load on Crankshaft	N [lb]	0 [0]
Crankshaft Radial Load Limit.....	MAB 0.01.09-12/02/2005	
Max. Allowable Radial Load on Front of Crankshaft		
At All Angles	N [lb]	2077 [467]
Max. Allowable Radial Load on Rear of Crankshaft		
At All Angles	N [lb]	2019 [454]
Maximum Operating Angles (see MAB No. 0.16.00-01/18/2007 for definitions and options to gain greater capability)		
Continuous Pitch Angle		
Engine Front Up From Horizontal	Deg.	10°
Engine Front Down From Horizontal	Deg.	4°
Continuous Roll Angle		
"Right" from vertical viewed from flywheel end of engine.....	Deg.	20°
"Left" from vertical viewed from flywheel end of engine.....	Deg.	20°
Intermittent Pitch Angle (intermittent operation less than 1 minute)		
Engine Front Up From Horizontal	Deg.	30°
Engine Front Down From Horizontal	Deg.	30°
Intermittent Roll Angle (intermittent operation less than 1 minute)		
"Right" from vertical viewed from flywheel end of engine.....	Deg.	45°
"Left" from vertical viewed from flywheel end of engine.....	Deg.	45°

FUEL SYSTEM

Maximum Allowable Restriction to Fuel Pump		
Clean Filter	kPa [in Hg]	14 [4.0]
Dirty Filter	kPa [in Hg]	27 [8.0]
Maximum Allowable Return Line Pressure	kPa [in Hg]	22 [6.5]
Maximum Static Pressure at Fuel Pump	kPa [in Hg]	20 [6.0]
Maximum Height of Fuel In Tank Above Fuel Pump	m [ft]	2.47 [8.1]

EXHAUST SYSTEM

Maximum Allowable Back Pressure	kPa [in Hg]	10 [3]
Maximum Bending Moment at Turbine Outlet Mounting Flange	N·m [ft·lb]	15 [11]
Maximum Incremental Direct Load at Turbine Outlet Mounting Flange	kg [lb]	6 [13]

AIR INDUCTION SYSTEM

Max. Allowable Intake Restriction - Turbocharged		
Clean Filter	kPa [in H ₂ O]	4 [15]
Dirty Filter	kPa [in H ₂ O]	6 [25]
Maximum Air Cleaner Inlet Temperature Rise Over Ambient	°C [°F]	17 [30]

Cummins Marine

Marine Engine General Data Sheet

LUBRICATION SYSTEM

Oil Consumption Rate (Volume Percent of Fuel Consumption Rate)	%	0.00
Oil Pressure at Normal Operating Temperature		
Idle Speed - Minimum in Main Oil Gallery	kPa [psi]	138 [20]
Rated Speed - Measured in Main Oil Gallery (Low)	kPa [psi]	310 [45]
Rated Speed - Measured in Main Oil Gallery (High)	kPa [psi]	483 [70]
Max. Allowable Oil Temperature (Sump)	°C [°F]	121 [250]
Oil Pan Capacity (Shallow) OP		
Low	liter [gal]	87.1 [23.0]
High	liter [gal]	113.6 [30.0]
Total System Capacity (Max. Sump + Filter(s))	liter [gal]	124.2 [32.8]
Oil Pan Capacity (Deep) OP		
Low	liter [gal]	128.7 [34.0]
High	liter [gal]	185.5 [49.0]
Total System Capacity (Max. Sump + Filter(s))	liter [gal]	196.1 [51.8]
By-Pass Oil Filter Capacity	liter [gal]	4.5 [1.2]

COOLING SYSTEM

Coolant Capacity		
Engine Only	liter [gal]	119.2 [31.5]
Engine Including Heat Exchanger and Integral Expansion Tank	liter [gal]	155.2 [41.0]
Min. Coolant Makeup Capacity	liter [gal]	23.8 [6.3]
Max. Pressure Drop Across Any External Cooling System Circuit	kPa [psi]	34.5 [5.0]
Max. Allowable Block Coolant System Pressure	kPa [psi]	103.4 [15.0]
Max. Coolant Temperature at Engine Outlet	°C [°F]	96 [205.0]
Min. Block Coolant Temperature (Warm Engine)	°C [°F]	71 [160.0]
Min. Allowable Coolant Expansion Space	% of System Capacity	5%
Maximum Sea Water Pressure	kPa [psi]	103.4 [15.0]
Maximum Sea Water Inlet Restriction	kPa [in Hg]	33.9 [10.0]
Sea Water Pump Specifications	Refer to MAB 0.08.17 - 07/16/2001	

ELECTRICAL AND STARTER SYSTEM

Electrical		<u>12V</u>	<u>24V</u>
Min. Recommended Battery Capacity			
Cold Cranking Amperes Rating (CCA)		N/A	1800
Marine Cranking Amperes Rating (MCA)			2250
Reserve Capacity (Discharging 25 Amps @ 80°F)	minutes	320	320
Min. Allowable System Voltage (@ Battery While Running)	Volts	12.0	24.0
Min. Allowable System Voltage (@ Battery While Cranking)	Volts	N/A	18
Max. Allowable System Voltage (@ Battery While Running)	Volts	15.5	31.0
Max. Allowable Voltage Drop of Starting Circuit (While Cranking)	Volts		2.6
Min. Engine Cranking Torque	ft-lb	N/A	1400
Min. Break-away Engine Cranking Torque	ft-lb	N/A	1000
Min. Engine Cranking Speed	rpm	150	150

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

TONTEK POWER LIMITED

ADD:NO.19,Hailing Industrial Area,Taizhou,Jiangsu,China

Tel:+86-523-81556166 Fax:+86-523-81558066

www.tontekpower.com

E-mail:info@tontekpower.com