



**TONTEKPOWER**  
www.tontekpower.com

# TPD1125H6.3 TECHNICAL DATA

DIESEL GENERATING SET

## TONTEK POWER LIMITED

**GREEN POWER SUPPLIER**



ISO9001:2008  
TONTEK POWER LIMITED



**50HZ**

[www.tontekpower.com](http://www.tontekpower.com)

Page: 1/10

Specifications may change without Notice

## TPD1125H6.3



**1125KVA/900KW  
POWERED BY CUMMINS**

## Diesel Generating Set

| MODEL            |               | TPD1125H6.3 |      |
|------------------|---------------|-------------|------|
| Power<br>Pf. 0.8 | Standby power | kVA         | 1250 |
|                  |               | kW          | 1000 |
|                  | Prime power   | kVA         | 1125 |
|                  |               | kW          | 900  |

Standby power: Continuous running at variable load for duration for an emergency. No overload is permitted on these ratings. In accordance with ISO 3046.

Prime power: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hours period. In accordance with ISO 8528, ISO 3046

### Features:

- Excitation system: self-excited (AREP and PMG are optional)
- ATS (automatic transfer switch) receptacle (optional)
- Lockable battery isolator switch
- Stainless galvanized zinc plates with strong corrosion resistance
- Vibration isolators between the engine/alternator and base frame
- Integrated wiring design
- Base fuel tank for at least 8 hours running
- Equipped with an industrial muffler
- Engine oil pump
- 50°C radiator
- Top lifting and steel base frame with forklift holes
- Drainage for fuel tank
- Complete protection functions and safety labels
- IP54 (soundproof sets), IP56 (control system)
- Water jacket preheater, oil heater and double air cleaner, etc. are available.



## Ratings and Performance Data

|                               |            |
|-------------------------------|------------|
| Cummins Engine Model          | KTA38-G9   |
| Alternator Model              | FDH5603C-6 |
| Frequency                     | 50Hz       |
| Rated speed                   | 1000 RPM   |
| Phase                         | 3          |
| Rated voltage                 | 400/630 V  |
| Fuel consumption at 100% load | 194.32L/h  |
| Noise dB(A) @7m (silent type) | 75         |

**Remark:** Also available in the following voltages 415/240V-380/220V-220/127V-200/115V;

## Dimensions and Weights

| Generating Set Type | Length (L)<br>mm | Width (W)<br>mm | Height (H)<br>mm | Weight<br>kg |
|---------------------|------------------|-----------------|------------------|--------------|
| Open Type           | 5200             | 2090            | 2320             | 10800        |



Open type

## Diesel Engine Data

### CUMMINS BRAND

|                                    |                            |
|------------------------------------|----------------------------|
| Model                              | KTA38-G9                   |
| Prime Power                        | 990kW/1237.5kVA            |
| Standby Power                      | 1089kW/1362kVA             |
| Total Displacement                 | 37.8Liter                  |
| Number of Cylinder and Arrangement | 12 – V type                |
| Engine Speed                       | 1000 rpm                   |
| Cycle                              | Four stroke                |
| Bore and Stroke                    | 159 x 159mm                |
| Compression Ratio                  | 13.9: 1                    |
| Aspiration                         | Turbo,Air/Water cooling    |
| Steady Speed Droop (%)             | ≤1%                        |
| Fuel Consumption at 100% load      | 199 g/kW.h                 |
| Governor                           | Electronic                 |
| Cooling System                     | Forced Water Cooling Cycle |
| Coolant Capacity                   | 280Liter                   |
| Total Lubrication System Capacity  | 135 Liter                  |

## AC Alternator Data

### FARADAY BRAND

|                          |                                           |
|--------------------------|-------------------------------------------|
| Alternator model         | FDH5603C-6                                |
| Exciter type             | Brushless , self-exciting                 |
| Frequency                | 50HZ                                      |
| Rated Speed              | 1000 rpm                                  |
| Design                   | Brushless single bearing, revolving field |
| Prime Power              | 900 kW                                    |
| Standby Power            | 990 kW                                    |
| Phase                    | 3                                         |
| Rated Voltage            | 400/630 V                                 |
| Power Factor             | 0.8                                       |
| Protection Grade         | IP23                                      |
| Insulation Grade         | H                                         |
| Voltage adjust range     | ± 5.0%                                    |
| Voltage regulation NL-FL | ≤1.0%                                     |

## **SPECIALLY ADAPTED FOR APPLICATIONS**

The alternator is designed to be suitable for typical generator applications, such as: stand-by, prime power, cogeneration, marine, rental, telecommunications, etc.

## **COMPLIANT WITH INTERNATIONAL STANDARDS**

The alternator conforms to the main international standards and regulations:

IEC 60034, NEMA MG 1.22, ISO 8528, CSA/UL request, marine regulations, etc.

It can be integrated into a CE marked generator-set.

The alternator is designed, manufactured and marketed in an ISO 9001 environment and ISO 14001.

## **TOP OF THE RANGE ELECTRICAL PERFORMANCE**

- Class H insulation.
- Standard 12-wire re-connectable winding, 2/3 pitch, type no. 6 (available in two versions: 6-wire and 12-wire).
- Voltage range: 220 V - 240 V and 380 V - 415 V (440 V) - 50 Hz / 208 V - 240 V and 380 V - 480 V - 60 Hz.
- Other voltages are possible with optional adapted windings:
  - 50 Hz: 440 V (no. 7), 500 V (no. 9), 600 V (no. 23), 690 V (no. 52)
  - 60 Hz: 380 V and 416 V (no. 8), 600 V (no. 9).
- THD Total harmonic distortion < 2% (full load).
- R 791 interference suppression conforming to standard EN 55011 group 1 class B standard for European zone (CE marking).

## **PROTECTION SYSTEM SUITED TO THE ENVIRONMENT**

- The alternator is IP 23.
- Standard winding protection for clean environments with relative humidity  $\leq 95\%$ , including indoor marine environments.  
Options: - Filters on air inlet : derating 5%.
- Filters on air inlet and air outlet (IP 44) : derating 10%.
- Winding protections for harsh environments and relative humidity greater than 95%.
- Space heaters.
- Thermal protection for windings and shields.

## **REINFORCED MECHANICAL STRUCTURE USING FINITE ELEMENT MODELLING**

- Standard direction of rotation : clockwise when looking at the drive end view (engine side).  
Running unit anti-clockwise: a derate of 5% must be applied.
- Compact and rigid assembly to better withstand generator-set vibrations.
- Steel frame.
- Two bearing and single bearing versions designed to be suitable for engines on the market.
- Half-key balancing.
- Greased for life bearings (regreasable bearings optional)

## **ACCESSIBLE TERMINAL BOX PROPORTIONED FOR OPTIONAL EQUIPMENT**

- Easy access to the voltage regulator and to the connections.
- Possible clusion of accessories for paralleling, protection and measurement.
- 9-way terminal block for voltage reconnection.

## Control System

### TPC-DSE7310 (Standard)

All our diesel generator set have a control cabinet (the DEEP SEA module DSE7310 as standard) mounted on isolated support.

#### Main Features

- Manual and automatic mode
- Parameter configuration via RS-232 serial communication
- Remote control automatic start/shutdown
- Optional ECU control
- Optional CAN engines
- Optional speed sensor access
- PLC programming
- Operating temperature: -20°C to 70°C
- IP56 Rating
- Back-lit icon LCD display
- Power Save mode
- CAN and Magnetic Pick-up/Alt. versions available (specify on ordering)
- PC configurable
- 6 Digital inputs
- 4 Outputs (2 configurable on Magnetic Pick up/Alt., 4 configurable



#### Protecting Functions

- Over frequency / under frequency
- Over voltage / under voltage
- Over current
- Over speed /under speed
- Emergency stop
- Low oil pressure
- High water temperature
- Failure to start/Failure to stop
- Battery charger failure
- Comprehensive shutdown or warning on fault condition

#### The control module display

- Generator voltage
- Generator frequency
- Battery voltage
- Engine speed
- Load current
- Engine run-time Hours
- Engine oil pressure (Panel Meter)
- Engine coolant temperature (Panel Meter)

## Control System

### TPC-DSE 7320(Optional)

TPC-DSE 7320 is an advanced control module based on micro-processor, It is an Auto Mains (Utility) Failure Control Module(AMF), have been designed to start and stop generating sets that include electronic And non-electronic engines. Include the additional capability of being able to monitor a mains (utility) supply. when main is not available. It can automatically start the engine and close generating sets breaker automatically, Accurately measure various operational parameters and display all values and alarms information on the LCD. In additional, it can automatically open breaker, and shutdown the engine after the main supply recovers.

### Main Features

- AMF and ATS and communication and expansion function
- Designed to work with electronic or non-electronic or gas engine simultaneously. (support many kinds of engines ECU).
- Manual, Automatic, Test and remote control mode selectable.
- Monitoring and measuring operational parameters of the mains supply and genset.
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections and multiple parameters display.
- Includes 12 inputs and eight outputs. 8 inputs are configurable and 4 outputs are configurable.
- Can be programmed using the front panel or by using the PC software.
- Support twelve languages. The language was edited by customer.
- Graded protection: pre-alarm, shutdown and electrical trip, flexible setting.
- The module can be pre-set for four operating modes and protecting parameters.
- Add DSE860 or DSE865 module, internet network monitoring can be realized.
- The firmware can be updated automatically, so customer can have the latest version.




### The control module display

- Generator voltage
- Generator frequency
- Battery voltage
- Engine speed
- Load current
- Generator KVA, KW, PF
- Engine run-time Hours
- Engine oil pressure
- Engine coolant temperature
- Real time clock for time and date, overall run time

**specifications may change without notice**

## Standard Configuration

- Assembled by Cummins diesel engine and reputable alternator
- Radiator and fan with safety guard
- Automatic control panel and electricity output switch cabinet
- Built-in shock pad
- Strong and durable hi-strength base frame



- ① Diesel Engine
- ② Alternator
- ③ Water Tank Radiator
- ④ Control Panel
- ⑤ Electricity/output switch cabinet
- ⑥ Hi-strength Base Frame
- ⑦ Solenoid Switch

## Standard Supply Scope



**Muffler**



**Maintenance free battery**



**Bellow**



**Elbow and flange**

## Optional Supply Scope

### Engine

- Water Jacket Preheater
- Fuel-water separator
- Oil pump
- Oil preheater
- Battery preheater

### Alternator

- PMG excitation
- Space heater
- Winding Temperature Measuring

### Generator Set

- Tools with the machine
- Coolant (-30°C)

### Control System

- AMF function
- ATS control cabinet
- Double-frequency and double voltage
- Single phase
- ABB MCCB

### Fuel System

- 12 / 24 hour base tank (single wall)
- Dual wall base fuel tank
- Outside fuel tank
- Automatic fuel feeding
- Fuel level indicate

### Canopy

- Hired type
- Economy Oil heater
- Trailer



**ATS**



**Synchronization Panel**



**Silent Canopy**



**Trailer**



**External Daily Fuel Tank**



**Auto Fuel Pump**



**Fuel and water separator**



**Fuel Drain Pump**



**Lube Oil Heater**



**Coolant Heater**

## Contact Us

### TONTEK POWER LIMITED.

Add: No. 19, Hailing Industrial Area, Taizhou City,  
Jiangsu Province, China 225300

Tel: +86 523 81556166

Fax: +86 523 81558066

E-mail : [info@tontekpower.com](mailto:info@tontekpower.com)

Website : [www.tontekpower.com](http://www.tontekpower.com)



TONTEK POWER LIMITED reserves the right to make changes in model, technical specification, color, configuration and accessories without prior notice. Please contact the salesman before ordering.

DISTRIBUTED BY: